

Economy of the Round Dairy Barn


Wilber J. Fraser

The background of the lower half of the page is a vibrant blue. Overlaid on this is a complex, abstract pattern of thick, bright pink lines and shapes. The pattern consists of various geometric elements: horizontal and vertical lines, diagonal lines, right-angled turns, and several solid pink triangles of different sizes. Some lines form a grid-like structure, while others are more irregular and overlapping. The overall effect is a dynamic, modern, and somewhat architectural design.

Project Gutenberg

Economy of the Round Dairy Barn

Wilber J. Fraser



The Project Gutenberg eBook of Economy of the Round Dairy Barn

This eBook is for the use of anyone anywhere in the United States and most other parts of the world at no cost and with almost no restrictions whatsoever. You may copy it, give it away or re-use it under the terms of the Project Gutenberg License included with this eBook or online at www.gutenberg.org. If you are not located in the United States, you will have to check the laws of the country where you are located before using this eBook.

Title: Economy of the Round Dairy Barn

Author: Wilber J. Fraser

Release date: December 16, 2011 [eBook #38321]

Language: English

Other information and formats: www.gutenberg.org/ebooks/38321

Credits: Produced by Bryan Ness, Pat McCoy and the Online Distributed Proofreading Team at <http://www.pgdp.net> (This file was produced from images generously made available by The Internet Archive/American Libraries.)

*** START OF THE PROJECT GUTENBERG EBOOK ECONOMY OF THE ROUND
DAIRY BARN ***

UNIVERSITY OF ILLINOIS
Agricultural Experiment Station

BULLETIN NO. 143

**ECONOMY OF THE ROUND
DAIRY BARN**

By WILBER J. FRASER



URBANA, ILLINOIS, FEBRUARY, 1910

SUMMARY OF BULLETIN NO. 143

1. [Round barns would be more generally built if their advantages were known and if the few which have been erected had been rightly constructed.](#)Page 1.
 2. [The round dairy barn offers greater convenience in storing, handling and distributing the feed.](#)Page 5.
 3. [In the circular construction, much greater strength is secured with less lumber.](#)Page 6.
 4. [The material for rectangular barns costs from 34 to 58 percent more than for round barns of the same area and capacity.](#)Page 7.
 5. [Round and rectangular barns compared.](#)Page 11.
 6. [Round and rectangular barns, including silos, compared.](#)Page 13.
 7. [Detailed account, with illustrations showing how the round barn at the University was built.](#)Page 17.
 8. [Itemized statement of cost of a 60-foot round barn.](#)Page 29.
 9. [Brief descriptions with illustrations and plans of several round dairy barns in actual use.](#)Page 31.
 10. [Conclusions. The advantages of the round dairy barn are convenience, strength and cheapness.](#)Page 44.
-

ECONOMY OF THE ROUND DAIRY BARN

FULL SPECIFICATIONS AND DETAILED COST AND CONSTRUCTION OF THE NEW SIXTY-FOOT CIRCULAR DAIRY BARN AT THE UNIVERSITY. SAVING OF ROUND OVER RECTANGULAR BARNs.

NOTES ON SEVERAL ROUND BARNs ON DAIRY FARMS. ^[A]

BY W. J. FRASER, CHIEF IN DAIRY HUSBANDRY

The planning, construction, and arrangement of farm buildings do not usually receive the thought and study these subjects warrant. How many dairymen have compared a circular, 40-cow barn with the common rectangular building containing the same area? How many understand that the circular structure is much the stronger; that the rectangular form requires 22 percent more wall and foundation to enclose the same space; and that the cost of material is from 34 to 58 percent more for the rectangular building?

In a community in which everyone is engaged in the same occupation, one person is likely to copy from his neighbor without apparently giving a thought as to whether or not there is a better way.

In a district of Kane county, Illinois, a certain type of dairy barn is used by nearly everyone, while in the next county a distinctly different type prevails, and the dairy barns of another adjacent county differ from those of either of the former, simply because the early settlers of this particular locality came from an eastern state and started building the style of barn then common in Pennsylvania.

In a certain community in Ohio where a milk condensing factory is located, a large number of farmers have barns 36 × 60 feet, with an "L" the same size. The loft of the "L" is used for the storage of straw, and the cows run loose in the lower portion. These barns are all built on practically the same plan and are usually of the same size, and this is the only community known to the writer where this form of barn is used in this manner.

This tendency to imitate emphasizes the fact that men do not exercise sufficient originality. Because most barns are rectangular is no reason that this is the best and most economical form.

^[A] Special acknowledgment is made to Mr. H. E. Crouch and Mr. R. E. Brand for their assistance in working out the detailed data which are the bases for the economic comparisons of the round and rectangular barns made in this bulletin.

WHY MORE ROUND BARNs ARE NOT BUILT



FIG. 1. BARN NO. 5. 100 FEET IN DIAMETER, SCALE 20 FEET TO ONE INCH; SHOWING INCREASED MOW CAPACITY GIVEN BY SELF-SUPPORTING ROOF.

In an early day when lumber was cheap, buildings were built of logs, or at least had heavy frames. Under these conditions, the rectangular barn was the one naturally used, and people have followed in the footsteps of their forefathers in continuing this form of barn. The result is that the economy and advantages of the round barn have apparently never been considered. This is because they are not obvious at first sight, and become fully apparent only after a detailed study of the construction. For these reasons, the rectangular form still continues to be built, altho it requires much more lumber. As the price of lumber has advanced so materially in recent years, the possible saving in this material is a large item, and well worth investigating.

The objections to round barns have usually been made by those who have only a superficial knowledge of the subject, and do not really understand the relative merits of the two forms. To the writer's knowledge, there has never been published a carefully figured out, detailed comparison of a properly constructed circular barn with the rectangular barn.

The difficulty with most round barns that have been built, thus far, is that they do not have a self-supporting roof, and consequently lose many of the advantages of a properly constructed round barn. This is the principal reason why round barns have not become more popular. A straight roof necessarily requires many supports in the barn below. These are both costly and inconvenient, and make the roof no stronger than a dome-shaped, self-supporting roof which nearly doubles the capacity of the mow. See [Fig.\(1\)](#).

Many who have thus disregarded capacity have also wasted lumber and made a needless amount of work by chopping or hewing out the sill and plate, thus requiring more labor and lumber, besides sacrificing the greater strength of a built-up sill. Rightly constructed round barns are, however, being built to a limited extent. One contractor has erected twenty-four round barns, with self-supporting roofs, in the last nine years. These barns

vary in size from 40 feet in diameter with 18-foot posts to 102 feet in diameter with 30-foot posts.

Another reason for the scarcity of round barns is the difficulty in getting them built. Most carpenters hesitate to undertake the work because in the erection of a round barn the construction should be entirely different from that of the rectangular form. Many new problems present themselves, but when these are once understood, the round barn offers no more difficulties in construction than the rectangular form. It is, however, important to have a head carpenter who is accustomed to putting up round barns, as a man with ingenuity and experience can take advantage of many opportunities to save labor and material.

KIND OF BARN NEEDED

The first thing to consider in the erection of a barn is a convenient arrangement for the purpose for which it is to be used. At the University of Illinois, two years ago, a twenty-acre demonstration dairy farm was started, the sole object being to produce the largest amount of milk per acre at the least possible cost. To meet the requirements of a barn for this purpose, it became imperative to build one that was convenient for feeding and caring for the cows, economical of construction, and containing a large storage capacity in both silo and mow. These are the requirements of a barn for every practical dairyman.



FIG. 2. FILLING THE SILO.

A silo was needed that could be fed from the year round. With the small number of cows kept, a deep enough layer of silage could not be fed off each day to keep it good thru the summer, if the silo was more than 12 feet in diameter. As this small diameter was a necessity, it would require two silos 33 feet deep to supply enough silage. Two silos of such small diameter would not only be costly, but difficult to make stand, unless built of concrete. This difficulty was overcome by using the circular barn and placing in the center a silo which is 12 feet in diameter and 54 feet deep, thus making the one silo, with as much capacity as the two before mentioned, answer every purpose. This deep silo is an important part of the round barn, as it not only forms a support for the roof, but is protected by the barn, thus saving the cost of siding. Then, too, besides occupying the space least valuable for other purposes, it being centrally located, is in the most convenient place for feeding. The silage chute being open at the top forms a suction of air, which

keeps the silage odor from the barn at milking time, and also assists in ventilation when the door to the chute is open.

ADVANTAGES OF THE ROUND BARN

The points of superiority that the round dairy barn shows over the rectangular form are convenience, strength, and cheapness.

ROUND BARN MOST CONVENIENT

Considering that the barn on a dairy farm is used twice every day in the year, and that for six months each year the cows occupy it almost continuously, and that during this time a large amount of the labor of the farm is done inside the barn, it is evident that the question of its convenience is a vital one. The amount of time and strength wasted in useless labor in poorly arranged buildings is appalling. People do not stop to consider the saving in a year or a lifetime by having the barn so conveniently arranged that there is a saving of only a few seconds on each task that has to be done two or three times every day.




FIG. 3. INTERIOR OF BARN, SECOND FLOOR, SHOWING SILO AND LOCATION OF ENSILAGE CUTTER. (TEAM UNHITCHED TO SHOW CUTTER.)

The round barn has a special advantage in the work of distributing silage to the cows. The feeding commences at the chute where it is thrown down, and is continued around the circle, ending with the silage cart at the chute again, ready for the next feeding. The same thing is true in feeding hay and grain.

Still another great advantage is the large unobstructed hay mow. With the self-supporting roof, there are no timbers whatever obstructing the mow, which means no dragging of hay around posts or over girders. The hay carrier runs on a circular track around the mow, midway between the silo and the outside wall, and drops the hay at any desired point, thus in no case does the hay have to be moved but a few feet, which means a saving of much labor in the mowing.

To successfully embody all of the above discussed advantages in a dairy barn is one of the large problems in milk production. In a careful study of the barn question it soon became apparent that it was impossible to embody all of the requirements advantageously in anything but a circular form of building, and the 60-foot round barn, which is here described, was built.



FIG. 4. SOUTH VIEW, SHOWING WELL LIGHTED STABLE.

CIRCULAR CONSTRUCTION THE STRONGEST

The circular construction is the strongest, because it takes advantage of the lineal, instead of the breaking strength of the lumber. Each row of boards running around the barn forms a hoop that holds the barn together. A barrel, properly hooped and headed, is almost indestructible, and much stronger than a box, altho the hoops are small. This strength is because the stress comes on the hoops in a lineal direction. Any piece of timber is many times stronger on a lineal pull than on a breaking stress. Take for example a No. 1 yellow pine 2×6 , 16 feet long, with an actual cross section of $1\frac{5}{8} \times 5\frac{5}{8}$ inches. If placed on edge and supported at the ends, as a joist, the limit of safety for a load evenly distributed is 642 pounds, while the limit of safety for a load in the lineal direction of the same piece of timber is 12,800 pounds, or twenty times as great.




FIG. 5. IN COW STABLE, SHOWING SILO AND FEED ALLEY IN CENTER OF BARN; STANCHIONS ON RIGHT, MILK SCALES AND RECORD SHEET ON LEFT.

All exposed surfaces of a round barn are circular, as both the sides and roof are arched, which is the strongest form of construction to resist wind pressure; besides, the wind, in striking it, glances off and can get no direct hold on the walls or roof, as it can on the flat sides or gable ends of a rectangular structure. If the lumber is properly placed in a round barn, much of it will perform two or more functions. Every row of siding boards running around the building serves also as a brace, and the same is true of the roof boards and the arched rafters. If the siding is put on vertically and the roof built dome-shaped, no scaffolding is required inside or out. These are points of economy in the round construction.

RECTANGULAR BARNs REQUIRE 34 TO 58 PERCENT MORE MATERIAL

In order to compare the amount and cost of material in round and rectangular barns, the following figures have been carefully worked out by an expert barn builder. Two comparisons, based on wood construction thruout, are made, in which round barns 60 feet and 90 feet in diameter are compared with both plank and mortise frame rectangular barns containing the same number of square feet of floor space, respectively. Since the most practical width of a rectangular dairy barn is 36 feet, its length will depend upon the number of square feet required in the barn.




FIG. 6. SHOWING CONSTRUCTION OF MORTISE FRAME BARN, END VIEW.




FIG. 7. SHOWING CONSTRUCTION OF PLANK FRAME BARN, SIDE VIEW.

[Figures 6](#) to [9](#) are side and end views, showing the detail construction and size of the timbers of the plank frame and mortise frame barns here figured. The detailed figures of the lumber bills for each of these barns were carefully worked out, but are too voluminous for publication here. The total number of feet of each kind of lumber required is given in [Tables 1A](#) and [1B](#). Since the proportion of the different kinds of lumber and shingles

varied for the different barns, to draw an exact comparison it was necessary to base it upon the money value, and for this purpose the total cost of lumber has been figured in each case. The lumber values used thruout are the best average prices that could be obtained. As the same prices are used for the material of all the barns, the comparisons of cost are correct, altho these exact prices will not hold for all localities and all times.




FIG. 8. SHOWING CONSTRUCTION OF PLANK FRAME BARN, END VIEW.

Since a silo cannot be economically built inside of a rectangular barn, the first comparison is made with the barns simply enclosed, altho one of the chief advantages of a round barn is the deep silo which it is possible to build so economically in the center.




FIG. 9. SHOWING CONSTRUCTION OF MORTISE FRAME BARN, SIDE VIEW.

Another item of economy in the circular barn is less framing lumber. This form has the strongest possible construction with the least lumber in the frame, and the least bracing, not a single timber larger than a 2 × 6 being required above the sill. The arched circular roof requires no supports, and no scaffolding is needed inside during its construction.

The accompanying tables show the comparative amount and value of lumber and cubical content in round barns 60 and 90 feet in diameter, and rectangular barns of equal area and height of posts.

TABLE 1A.—A COMPARISON OF THE COST OF MATERIAL IN ROUND AND RECTANGULAR BARNs OF THE SAME AREA, *Not Including* FOUNDATION AND SILOS

	Round Barn 60 feet in diameter	Rectangular barn, 36 × 78½ ft.	
		Plank frame	Mortise frame
Framing lumber	13,976 ft. @ \$25 = \$349.40	19,833 ft. @ \$25 = \$495.83	29,074 ft. @ \$25 = \$726.85
Sheathing, siding, and flooring	12,971 ft. @ \$22 = 285.36	15,355 ft. @ \$22 = 337.81	15,355 ft. @ \$22 = 337.81
Shingles	44,000 @ \$3.75 = 165.00	45,000 @ \$3.75 = 168.75	45,000 @ \$3.75 = 168.75
Bolts		20.88	
Total cost of lumber	\$799.76	\$1023.27	\$1233.41
Content, cubic feet	117,669	117,138	117,138

TABLE 1B.

Round barn, 90 feet in diameter	Rectangular barn, 36 × 176¼ ft.	
	Plank frame	Mortise frame

Framing lumber	30,899 ft. @ \$25 = \$772.48	38,815 ft. @ \$25 = \$970.38	59,481 ft. @ \$25 = \$1487.03
Sheathing, siding, and flooring	22,375 ft. @ \$22 = 492.25	28,547 ft. @ \$22 = 628.03	28,547 ft. @ \$22 = 628.03
Shingles	97,000 @ \$3.75 = 363.75	102,000 @ \$3.75 = 382.50	102,000 @ \$3.75 = 382.50
Bolts		26.76	
Total cost of lumber	\$1628.48	\$2007.67	\$2497.56
Content, cubic feet	322,952	270,570	270,570

ROUND AND RECTANGULAR BARNs COMPARED

In comparing the 60-foot round barn with a rectangular barn of the same area, the two barns should afford the cows the same amount of space on the platform. Allowing each cow in the 60-foot round barn 3 feet 6 inches in width at the rear of the platform, it will accommodate 40 cows and leave space for two passage ways. But in a rectangular barn, only 3 feet 4 inches of platform space need be allowed for each cow, and the 78½ foot barn, with two 3-foot passage ways across it for convenience in feeding, will accommodate 42 cows. While the rectangular barn has stall room for two more cows, the round barn contains space in the center for a silo 18 feet in diameter.

The floor space and cubical content of the round barn 60 feet in diameter, and the rectangular barn compared with it in these tables, are practically the same, and the barns are therefore directly comparable. This being true, the percentages which were figured from the complete bills of material for these barns show the exact saving in lumber on the 60-foot round barn over the plank and mortise frame rectangular barns 36 × 78½ feet. The lumber bills of the rectangular barns show an increase in cost of 28 percent for the plank frame and 54 percent for the mortise frame. The round barn, 60 feet in diameter, contains 188½, and the rectangular barn 225 lineal feet of wall. The rectangular barn has, therefore, 22 percent more lineal feet of outside barn wall, requiring a proportional increase in both paint and foundation.

The 176¾-foot rectangular barn would hold 100 cows, allowing each cow 3 feet 4 inches in width and providing for 3 passage ways of 3 feet each across the barn.

The 90-foot round barn would hold 100 cows in two rows headed together, 65 of which would be in the outer circle, and have 3 feet 6 inches each in width at the gutter. This leaves sufficient room for feed alleys and walks, and two passage ways, one three feet and the other seven feet wide for the manure and feed carriers. All of this is outside of a central space for a silo 20 feet in diameter and 71 feet high, with a capacity for 620 tons of silage, and in the mow there would still be an excess, above the capacity of the rectangular barn, of 33,000 cubic feet, which would hold 66 tons of hay, or as much as the entire mow of a barn 32 × 36 feet with 20-foot posts.

TABLE 2A.—A COMPARISON OF THE COST OF MATERIAL IN ROUND AND RECTANGULAR BARNs, Including FOUNDATION AND SILOS.

	Round barn, 60 feet in diameter	Rectangular barn, 36 × 78½ ft.	
		Plank frame	Mortise frame
Lumber in barn,	\$799.76	\$1023.27	\$1233.41
Material in foundation,	86.89	105.90	105.90

Material in silo,	159.01	295.26	295.26
Total cost of material in barn,	\$1045.66	\$1424.43	\$1634.57
Actual money saved,		\$378.77	\$588.91
Proportional cost,	100%	136%	156%

TABLE 2B.

	Round barn, 90 feet in diameter	Rectangular barn, 36 × 176¾ ft.	
		Plank frame	Mortise frame
Lumber in barn,	\$1628.48	\$2007.67	\$2497.56
Material in foundation,	130.35	196.80	196.80
Material in silo,	265.00	513.52	513.52
Total cost of material in barn,	\$2023.83	\$2717.99	\$3207.88
Actual money saved,		\$694.16	\$1184.05
Proportional cost,	100%	134%	158%

The square feet of floor space in the round barn 90 feet in diameter and rectangular barn 36 × 176¾ feet are the same, but the cubical content of the former is more than that of the latter. The increase in the lumber bill is 23 percent in the plank frame and 53 percent in the mortise frame barn. The round barn 90 feet in diameter contains 283 and the rectangular barn 426 lineal feet of wall. The rectangular barn has, therefore, 50 percent more lineal feet of outside barn wall, requiring a proportional increase in both paint and foundation.

The smaller surface on the outside wall of the round barn requires less paint and makes a proportional saving in keeping the round barn painted in after years.

ROUND AND RECTANGULAR BARNs, *Including Silos*, COMPARED

Owing to the fact that a silo is a necessity for the most economical production of milk, a barn is not complete for a dairyman's purpose unless it includes a silo with capacity to store sufficient silage for the herd. In the case of the round barn, the silo is most economically built inside, but in the rectangular form would cause a waste of space, and for that reason is best erected outside. Therefore, in comparing a round dairy barn with a rectangular dairy barn, silos should be included.

In figuring the cost of materials in the silos for the round and rectangular barns, the capacity needed in each case was determined in the following manner: Allowing 40 pounds of silage per cow per day for 7 winter months and 25 pounds per cow per day for 3 months during the summer, would require for 40 cows 220 tons; then allowing one-eighth for waste would make the silage requirement 248 tons. As the silo in the round barn 60 feet in diameter is 53 feet deep, it would need to be only 16 feet in diameter to hold 250 tons. This diameter is sufficiently small to allow summer feeding without waste. To erect a silo outside of a barn, with sufficient stability to stand well, the height above ground should not be much more than twice the diameter, and in order to avoid waste for summer feeding, the diameter should not be greater than 16 feet for a herd of 40 cows. In order that a deep enough layer of silage can be fed off each day during the summer to avoid waste, it is evident that to store 250 tons of silage outside the barn, two silos would be required. One of these should be 16 feet in diameter and 36 feet deep, holding 154 tons, and the other 13 feet in diameter and 36 feet deep, holding 102 tons, making a total silo capacity of 256 tons.

As the large barns hold 100 cows, the same allowance of silage per cow for the season would require silo capacity for 620 tons. As the silo in the round barn 90 feet in diameter would be 71 feet deep, it would need to be only 20 feet in diameter to hold 620 tons. To

store 620 tons of silage in silos built outside the rectangular barn would require two silos, each 20 feet in diameter and 44 feet deep.^[B] These are the sizes on which the figures for cost of silos of the Gurler type, given in [Tables 2A](#) and [2B](#), were used.




FIG. 10. INTERIOR OF COW STABLE, SHOWING WATER TROUGH WITH FLOAT VALVE, SALT BOX, AND DOOR INTO DAIRY.

The table ([page 12](#)) is the final summing up of the cost of all the material for the completed dairy barns, with silos, and shows a saving of from 34 to 58 percent in favor of the round barn and silo, or an actual money saving in this case of from \$379 to \$1184, depending upon the size and construction of the barns.

Thoughtlessly, men go on building rectangular barns, but what would this reckless disregard of a possible saving of 34 to 58 percent mean in a year's business on the farm? Some illustrations may help us to understand what this money saved in building a round barn really amounts to, and its convenience is also a great saving. If the dairyman discarded the idea of a rectangular barn and built a round barn instead, he could take the money thus saved and buy one of the best pure-bred sires for his herd, and also three to ten pure-bred heifers or fine grade cows. Either of these purchases might double the profit of the herd. Or, this saving, properly applied, would purchase many labor-saving devices which would make life less of a drudgery on many dairy farms. Is not such a saving worth while?




FIG. 11. COW COMFORT IN A ROUND BARN.

When the comparative cost and merit of two constructions are known, it is a poor financier who will pay extra for the one which is inferior. If a man received bids from contractors for a building, he would be a foolish man who would accept one which is from 34 to 58 percent higher than the lowest bidder, especially when he knew the lowest bidder would put up the most convenient and substantial building.

[B] Since the deeper the silo the more firmly the silage packs, one silo 71 feet deep will hold as much as two silos of the same diameter and 44 feet deep.

DISADVANTAGES OF THE ROUND DAIRY BARN

The disadvantages of the round dairy barn are, that it cannot be enlarged by building on as readily as can the rectangular form, but as the round barn may be built higher to the eaves than a rectangular barn 36 feet wide, provision can be made for the growth of the herd by building so as to put cows in the second story and still leave sufficient mow room for hay.

The objection is frequently raised that a round barn is difficult to light. This difficulty is entirely overcome in a barn 90 feet or less in diameter, if a sufficient number of properly spaced windows are used. See [Figs. 4](#) and [30](#). With the same number of windows, the light is more evenly distributed in a round barn and the sun can shine directly into some portion at all hours of the day during the winter.




FIG. 12. FIRST STORY WALL, AND FOUNDATION FOR SILO, FEED ALLEY, AND MANGER; SILL IN PLACE, READY FOR JOISTS AND STUDS.

The objection has been raised that rectangular objects cannot be placed in a circle without a waste of space, but this does not apply to a dairy barn, as the storage of hay and grain depends upon cubical content, alone, and silos should always be circular, no matter where built. Cows, when lying down, are decidedly wedge-shaped, requiring much less space in front than behind. The objection may be raised, with round barns large enough for two rows of cows, that the row headed out does not use the space as economically as in the rectangular form, because a cow needs more width at the rear of the platform than at the manger. Where there are two rows of cows, the inner row is usually headed out, and as only about one-third of the cows are in this row, this loss of space is counterbalanced by the large number of cows in the outer circle using the space more economically than they do in the rectangular barn.

Box stalls cannot be as conveniently arranged, but in a one-row barn, gates hung on the outside and swung around to the manger, form stalls for cows at freshening time, and in a barn with two rows, box stalls can be arranged in the inner circle.

HOW THE ROUND BARN AT THE UNIVERSITY WAS BUILT

The barn is located on the side of a hill, sloping gently to the south and east. With this location, it was an advantage to excavate 5 feet deep on the northwest and run out to the surface of the ground on the southeast.




FIG. 13. SHOWING TEMPORARY BRACING TO HOLD STUDS IN PLACE WHILE SHIP LAP CEILING IS NAILED ON.

The footing for the foundation is 18 inches wide. A ten-inch brick wall was carried up nine feet above the stable floor. This wall contains a 2-inch air space to prevent moisture from condensing on the inner wall and making the barn damp. This is an important point, as barns with a solid stone or brick wall are very objectionable on account of dampness. It has been proven by two years' use that this difficulty is entirely obviated by the air space in the wall.

The foundation for the manger and feed alley is built up 2 feet above the stable floor. The foundation for the silo extends 4 feet below the stable floor and is continued 9 inches above the floor in the feed alley. This silo wall, together with the foundation under the manger, forms the foundation for the center supports of the barn. [Fig. 12](#) shows the foundation completed.

The silo, which is the Gurler type, was then started and carried up with the barn. It was built by placing 2×4 studs around the circle, one foot on centers, and ceiling inside with $\frac{1}{2} \times 6$ -inch lumber. This $\frac{1}{2}$ -inch lumber was obtained by re-sawing 1×6 yellow pine fencing. Common lath were then put on horizontally in the regular way inside, without furring out, and plastered with rich cement plaster.

The sill of the barn is 6×6 , made up of 1×6 s, and built on top of the wall. Building it up in this manner makes a stronger sill than can be obtained in any other way, as it forms a continuous hoop around the barn.



FIG. 14. SHOWING HEIGHT AND CONSTRUCTION OF SILO, SIDING COMPLETED, AND FOUR MAIN RAFTERS IN PLACE.

The joists are 2×12 s notched 6 inches to fit the sill, so that the outer ends rest on both the sill and the brick wall. The outer span of joists is 14 feet and the inner ends of these joists rest on a similar sill built of 1×6 s on top of the 4×4 supports at the stanchions. The inner span of joists, between the stanchions and the silo, is 8 feet, the outer end resting on the sill over the stanchions, and the inner end on a $1\frac{1}{2} \times 6$ -inch band, made up of three $\frac{1}{2} \times 6$ -inch pieces, running around the outside of the silo. These joists are placed $2\frac{1}{2}$ feet apart at the outside of the barn, and half as many joists are used in the inner span, making the joists at the silo one foot apart. The number of joists under the driveways are doubled, being only 1 foot and 3 inches apart at the outside of the barn.




FIG. 15. SHOWING ALL RAFTERS IN PLACE AND METHOD OF SHEATHING ROOF.

The studs, which are 2×6 s, 20 feet long, were then placed on the sill, about 2 feet 6 inches apart, being as evenly spaced between the windows as possible, and temporarily braced, as shown in [Fig. 13](#), until the 8-inch ship lap ceiling could be nailed on the outside. This was carried up 5 feet to the second scaffold, and then covered to this height with shingles laid 5 inches to the weather. The scaffolding was then moved up and this process repeated until the siding was completed. The plate, made up of five 1×4 s, was then built in the notch in the top of the studs shown in [Fig. 13](#).




FIG. 16. SHOWING HEIGHT OF SILO, CAPACITY OF BARN, AND CONSTRUCTION OF ROOF.

The silo was completed, as before described. The rafters, which were framed on the ground, were then erected, as shown in [Fig. 14](#), the first eight going to the center of the roof, and the remaining ones were cut to rest on the plate of the silo. There are 64 framed rafters, and these are the only ones in the upper section of the roof. At the break in the roof, a header is cut in between the framed rafters, and in the lower section a rafter is placed between these, thus making twice as many rafters in the lower section of the roof as in the upper section. After the rafters were all in place and temporarily braced, the 1 × 2-inch sheathing was put on, as shown in [Fig. 15](#), and the shingles, which were the best $\frac{5}{2}$ red cedar, were laid 5 inches to the weather on the lower section of the roof, and 4 inches to the weather on the upper section, as this had less pitch. No chalk line was necessary, as the shingles were laid by the sheathing.




FIG. 17. SHOWING ARRANGEMENT OF JOISTS AND HOW THE FLOOR IS LAID.

The floor was made of 1×8 ship lap, laid in four directions, as shown in [Fig. 17](#). In the driveway an extra layer of ship lap was used, making this portion of the floor 2 inches thick.

The doorways in the second story are 14 feet wide, and in the lower story 12 feet. These openings are closed by two sliding doors, each door being made of two sections, hinged together so as to follow the circular wall of the barn in opening.

The cow stable is on the ground floor, and well lighted by 16 windows having twelve 9×12 lights each. There are also six windows in the doors. The windows are placed just below the ceiling and admit an abundance of sunshine at all times of the day, which is one of the essentials of a good dairy barn.




FIG. 18. SHOWING PRESENT ARRANGEMENT OF COW STABLE. THERE ARE STANCHIONS AND MANGERS FOR 28 COWS, AND 2200 SQ. FT. OF FLOOR SPACE IN WHICH THE COWS CAN RUN LOOSE. THE GATES ARE SWUNG INTO THE PRESENT POSITION WHEN BOX STALLS ARE NEEDED.

The floor, back of the manger, is of clay, except at the door, where a small portion is covered with cement. The cows run loose except at feeding and milking time, when they are placed in rigid stanchions. It must be distinctly understood that rigid stanchions are strongly condemned as a cow tie, where cows are to remain in them all night, but as they are here used merely to hold the cow during milking, they are both economical and convenient.




FIG. 19. SHOWING CROSS SECTION OF 60-FOOT ROUND BARN.




FIG. 20. CLEANING OUT COW STABLE WITH THREE-HORSE MANURE SPREADER.




FIG. 21. COWS IN STANCHION AT MILKING TIME.

Running cows loose in this manner is an excellent method, where bedding is abundant and sufficient space is available, as the cows are more comfortable, and all fertility is saved. There is no waste from leaching, as when the manure lies exposed to the weather. This method saves the labor of cleaning the stable, as the manure is loaded into the spreader and hauled directly upon the land whenever convenient, and the land is in the best condition to receive it.^[C]

Three gates are hung on posts at the outside wall, and when box stalls are needed, these are swung around to the manger, as shown in [Fig. 18](#). The south door in the cow stable can be closed by slatted gates, thus affording an abundance of fresh air and sunshine on nice days, without letting the cows out of the barn.

^[C] For a more detailed discussion of the advantages of keeping cows in this manner, see Illinois Agricultural Experiment Station Circular No. 93.

SYSTEM OF VENTILATION




FIG. 21. CONTINUED.

The system of ventilation is the "King." To economize space and lumber, the hay chute is used for a ventilator. This chute, which extends to the cupola, is $2\frac{1}{4} \times 3\frac{1}{2}$ feet, having a cross section area of 8 sq. ft., which, with a good draft, is sufficient for 40 cows. In order that this combination of ventilator and hay chute prove practical, doors thru which the hay could be thrust were placed at intervals in the side of the chute. These doors are hinged at the top, opening in, and close immediately after the hay drops, thus maintaining a closed ventilator chute. The air is drawn in at the bottom, the amount being regulated by means of a sliding door in the side. As this chute is 50 feet high, it creates a strong suction.

THE MILK ROOM

To economize space, the milk room, 12×16 feet, is located under the north driveway. The brick walls under the drive form the sides of this room, and the floor of the drive, which is made of 2×6 s grooved on both edges, forms the roof. The grooves in the flooring were filled with white lead, and a wooden strip, fitted to fill the grooves of both planks, was driven in, forming a water-tight floor. This floor was covered with hot tar and sand $\frac{1}{2}$ inch thick. The milk room is plastered on the inside, the plaster being applied directly to the brick walls, excepting in the case of the ceiling, which is lathed. The floor and cooling tank are of cement. The passage from the barn to the milk room is thru a small hallway, which is open to the outside, thus preventing the stable air getting into the milk room.




FIG. 22. FEED ALLEY, SHOWING COMBINED HAY CHUTE AND VENTILATOR. A DOOR ON THE SIDE WHICH IS HINGED AT THE BOTTOM, 3 FEET FROM THE FLOOR, IS LET IN TOWARD THE SILO, SLIDING THE HAY ONTO THE FLOOR. IN HOT WEATHER THIS OPENING TAKES THE HEAT OUT OF THE BARN; DURING THE WINTER THIS DOOR IS KEPT CLOSED AND THE VENTILATION IS REGULATED BY RAISING THE SLIDE, AS SHOWN IN THE CUT.

BARN SATISFACTORY

This round dairy barn above described has been in use for over two years at the University of Illinois, and has given entire satisfaction.



FIG. 23. NORTHEAST VIEW, SHOWING DAIRY UNDER DRIVEWAY. THE BARN IS ON THE SAME SCALE AS THE DRAWING ON [PAGE 28](#).



FIG. 24. INTERIOR OF DAIRY; COOLING TANK ON LEFT.

RE-ARRANGEMENT OF BARN TO ACCOMMODATE 40 COWS

If it is desired to keep cows in stalls in a round barn of this size, the circular manger can be enlarged to 38 feet in diameter, which gives room for forty cows, as shown in [Fig. 25](#), and the silo, to hold sufficient silage to feed the year round, enlarged to 18 feet in diameter. The present mow room is sufficient to store enough hay and bedding for this number of cows.

The barn on the Twenty-acre Demonstration Dairy Farm was built this large, as it was thought it might be desired at some future time to increase the size of the farm and herd, and the barn could easily be changed to accommodate a larger herd by simply enlarging the silo, without rebuilding the barn.




FIG. 25. SHOWING HOW THIS 60-FOOT BARN MAY BE ARRANGED TO ACCOMMODATE 40 COWS IN STALLS. TO SUPPLY THIS SIZED HERD AND THE NECESSARY YOUNG STOCK WITH SILAGE FOR EIGHT MONTHS WOULD REQUIRE A 370-TON SILO, OR ONE 18 FEET IN DIAMETER AND 56 FEET DEEP; WITH A SEVEN-FOOT FEED ALLEY AND A 2½-FOOT MANGER, THE CIRCLE AT THE STANCHIONS WOULD BE 38 FEET IN DIAMETER, OR 119⅓ FEET IN CIRCUMFERENCE; ALLOWING 4¼ FEET FOR TWO PASSAGE WAYS, THE STALLS WOULD BE 2 FEET 10-1/2 INCHES WIDE AT THE STANCHION, AND 3 FEET 6 INCHES AT THE DROP.

ITEMIZED COST OF THIS ROUND BARN

Excavating, foundation, and first story brick wall				\$904.00
Lumber:				
149 pieces,	1	× 4	× 16	Y. P.
31 "	1	× 4	× 14	Cypress
16 "	1	× 4	× 12	"
165 "	1	× 6	× 16	Y. P.
17 "	1	× 6	× 14	"
226 "	2	× 4	× 12	"
20 "	2	× 4	× 16	"
6 "	2	× 4	× 14	"
15 "	4	× 4	× 14	"
120 "	2	× 12	× 16	"

23	„	2	×	12	×	14	„		
100	„	2	×	6	×	20	„		
144	„	2	×	6	×	16	„		
67	„	2	×	6	×	18	„		
4	„	2	×	6	×	26	„		
60	„	2	×	6	×	12	„		
30	„	2	×	6	×	22	„		
4	„	2	×	6	×	24	„		
6	„	2	×	8	×	10	„		
9	„	2	×	8	×	16	„		
4	„	2	×	10	×	14	„		
11	„	2	×	10	×	12	„		
1	„	2	×	10	×	22	„		
1	„	1	×	10	×	12	„		
1	„	1	×	10	×	14	Cypress		
2	„	1	×	12	×	14	„		
22	„	1 1/8	×	8	×	10	Cyp. S2S		
2	„	1	×	1 1/8	×	12	×	14	„
2	„	1	×	1 1/8	×	12	×	16	„

- 6000 feet of 8-inch ship lap
- 3150 feet of 10-inch ship lap
- 71 M 1/2 red cedar shingles
- 165 Lineal feet of 2-inch Cr. molding
- 240 Lineal feet of Cr. molding
- 270 feet of 4-inch Y. P. S1S
- 4000 feet of 6-inch rough pine
- 62 feet of 3/8-inch Y. P. Ceiling
- 850 feet of 6-inch No. 1 flooring
- 230 feet of 6-inch fence flooring
- 56 lineal feet of 1/2 × 3-inch battening
- 32 lineal feet of lattice
- 444 lineal feet of 4-inch cypress
- 3 10-foot cedar posts

Total cost of lumber \$1,313.63

Mill work:

Window sash and doors	\$270.00
Window and door frames	71.00
Sawing lumber for silo, roof, bridge and stanchions	29.78
Cost of hardware	96.57

Carpenter work:

Head carpenter	518 hrs. @ 40c = \$207.20
Carpenters	1057 hrs. @ 35c = 369.95
Common labor	429 hrs. @ 20c = 85.80

Total cost for carpenter work	662.95
Tiling around barn and silo, sewer from dairy room, retaining wall, cement floor in alley, dairy, doorway of barn, and steps and tanks	128.54
Plastering dairy room and inside of silo	104.60
Painting	89.54
Total cost of barn	<u>\$3670.61</u>



FIG. 26. BARN NO. 2. 80 FEET IN DIAMETER; ENGINE ROOM IN FOREGROUND.

The cost of this barn, if built on the ordinary dairy farm, could be materially reduced without shortening the life of the barn. Owing to the conditions under which this barn was built, it was necessary to pay for hauling all material to the farm, two and one-half miles from town. All of the labor had to be hired, and as it was necessary for the men to board themselves the wages paid were proportionately higher. The farmer usually does the excavating and hauls the brick, sand, and lumber with his own teams, tends the mason, and does quite an amount of the rough work with his own help, besides boarding the men, all of which would greatly reduce the cost. The construction could also be cheapened by using drop siding to cover the outside, instead of shingles, which in this case were used over ship lap on the side walls to improve the appearance. This barn could be still further cheapened by putting hoops, five feet apart, around the studs, and covering with common 1 × 12 boards, put on vertically, as is done in some cases. A saving could also be made on the mill work and large doors by having the carpenters make these plainer and leave the windows out of them.

Anyone wishing to build a round barn can get local bids on the lumber bill, and determine approximately the cost in his locality. This will vary with both the location and the year.

OTHER ROUND DAIRY BARN

BARN NO. 2

Built 1897.

Diameter, 80 feet.

Capacity, 75 cows in 2 rows, tails together, 51 head in outer circle, 24 head in inner circle.




FIG. 27. INTERIOR OF BARN NO. 2, SHOWING TWO ROWS OF STANCHIONS AND DRIVE BEHIND COWS WHICH IS USED IN CLEANING BARN; SILO ON RIGHT.

Cost, \$1800.

Studs, 2×6 s, placed $2\frac{1}{2}$ feet on center.

Supports, two 2×6 s in each stanchion.

Joists, main span 3×12 s, 20 feet long, placed 14 inches on center. Short spans over feed alleys, 2×10 s.

Plate, 1×10 -inch boards sprung around near top of studs.

Roof supports, 6×6 s placed 12 feet apart. Purline plate rests on these posts and consists of 1×8 s sprung to the circle.

Siding, 8-inch, put on horizontally, first story ceiled inside.

To clean out, a wagon is driven around between the two rows of cows.

The chief objection to this barn is insufficient light in the cow stable.

This barn and No. 3 are approximately the same in construction, and are more substantially built than barns No. 4 and 5.




FIG. 28. ARRANGEMENT OF COW STABLE IN BARN No. 2; TWO ROWS OF COWS TAILED TOGETHER. THE BARN IS CLEANED BY DRIVING AROUND BEHIND THE COWS.



FIG. 29. BARN NO. 3. 80 FEET IN DIAMETER.

BARN NO. 4

Built in 1900.

Diameter, 90 feet.

Capacity, 105 cows, two rows heading together.

Cost, \$3000.

Foundation, width at base and top, 18 inches; depth in ground, 20 inches, (not sufficient).

Sills, 2×8 s, sawed in short lengths, and placed flatwise.

Studding, 20-foot 2×8 s, placed 3 feet on center and toenailed to sill.

Supports, first story 4×4 s placed between stanchions in each row, making two rows of supports between the outside wall and the silo; 4×4 s cut to a circle placed on top of these supports. The outside span, over cows, is 13 feet 6 inches; middle span, over feed alley, 6 feet 8 inches, and inside span, over cows, 13 feet.

Joists, 2×8 s placed 3 feet apart at studs on outside wall. There are as many joists in center of barn as at the outside.


Supports, second-story, consist of one row of posts running around at a point immediately under the break in the roof. These are 16 feet apart and are made of three 2×8 s kept 2 inches apart by horizontal braces which run from studding near the eave thru these posts to studding in silo. See [Fig. 31](#).

Plate, rafter is set on top of each stud, and no plate is used.

Rafters, 2×6 s resting on studs at outside and on circular plate at break in roof.



FIG. 30. BARN NO. 4. 90 FEET IN DIAMETER; ONE OF THE FEW DAIRY BARNs WITH SUFFICIENT LIGHT; SAME SCALE AS DRAWING ON [PAGE 37](#).



**FIG. 31. SILO IN CENTER OF BARN NO. 4;
UPPER PORTION IN HAY LOFT. LOWER
PORTION IN COW STABLE.**

Siding, 8-inch drop siding, put on horizontally, nailed with 10d nails. Ends holding well.

Windows, 12 light, 10 × 12 glass; one window every six feet. This gives an abundance of light in the center of the barn.

Doors, built on circle; (not satisfactory).

Silo, round; diameter, 24 feet over all; height, 53 feet, exclusive of 12-foot space for water tank on top; capacity, 500 tons. Studs of silo, 2 × 4s placed 12 inches on center. Ceiled inside of studs with two thicknesses of half-inch lumber with paper between.




FIG. 32. INTERIOR OF BARN NO. 4, SHOWING STALLS AND FEED ALLEY.

Remarks: Considering its size, the construction of this barn is apparently too light to be substantial, as the joists and studs are too small and too far apart, yet it has stood for nine years with no more evidence of wear than is common with any barn.

Were the owner to build again he would place the studs only 2½ feet apart and use 2 × 12 joists, 2½ feet apart at the outside wall. He would also use cement plaster on inside of silo.

The owner says it would have cost him as much to have built a rectangular barn without the 500-ton silo, and containing 1300 sq. ft. less floor space. In other words, he gained a 500-ton silo and 1300 sq. ft. of floor space, besides an immense amount of mow room, by building a circular barn.




FIG. 33. ARRANGEMENT OF COW STABLE IN BARN NO. 4, 90 FEET IN DIAMETER; TWO ROWS OF COWS HEADED TOGETHER.

BARN NO. 5

Built in 1906.

Diameter, 100 feet.

Capacity, 115 cows.

Cost, \$3400.

Studding, 16-foot 2×6 s, placed 3 feet on centers.

Supports, 3 rows 4×4 s.

Joists, 2×10 s, placed 3 feet on centers. Hemlock and yellow pine.

Floor, laid in eight directions.

Rafters, 2×6 s spiked to studs. A band of two 1×6 s is placed around the studs just below the rafters, and helps support the rafters.

Supports for roof. There are three purline plates. Two of these are supported by posts, the other by braces running out from the silo. The roof is straight from eaves to peak. The bracing is similar to that of barn No. 4.

Silo, 18 feet in diameter, 56 feet deep, 2 feet in ground. Capacity, 350 tons.



FIG. 34. BARN 92 FEET IN DIAMETER; TWO ROWS OF COWS HEADED TOGETHER; SILO IN CENTER.



FIG. 35. VIEW OF 70-FOOT SELF-SUPPORTING ROOF ON BARN SHOWN IN [FIG. 36](#); NOTE HOOPS ON STUDS IN RIGHT FOREGROUND.




FIG. 36. BARN 70 FEET IN DIAMETER; FRAME HOOPED FOR PERPENDICULAR SIDING; LOWER SECTION SIDED.

THE SMALL DAIRYMAN'S BARN



FIG. 37. BARN 40 FEET IN DIAMETER.




FIG. 38. BARN 48 FEET IN DIAMETER, 16-FOOT POSTS; NOTE METHOD OF TAKING HAY INTO SMALL ROUND BARN.

The round barns previously described do not meet the needs of the man with only a few cows. He usually wants a general-purpose barn. The circular form can be made satisfactory for this purpose if proper attention is given to the plan. It is necessary that the cow stable be distinctly separated from all other stock by a tight wall. Round barns with this arrangement are giving satisfaction in Illinois at the present time.




FIG. 39. SHOWING CONSTRUCTION OF BARN IN [FIG. 40](#). HOOPS IN PLACE READY FOR PERPENDICULAR SIDING; ROOF SHEATHED FOR SHINGLES.



FIG. 40. BARN 102 FEET IN DIAMETER AND 85 FEET HIGH.

DISADVANTAGES OF THE POLYGONAL BARN.

A polygonal barn has the disadvantages of both the rectangular and the round barn, and is less stable than either. It must necessarily have a heavy frame, which is expensive, and as the siding cannot run around the corners, it is very difficult to tie the different sides together sufficiently to prevent the barn being racked by the wind.

BARN NO. 6



FIG. 41. BARN NO. 6; 85 FEET IN DIAMETER; SAME SCALE AS DRAWING ON OPPOSITE PAGE.

16-sided.

Built, 1888.

Diameter, 85 feet.

Height, 26-foot posts on 9-foot wall.

Capacity, 88 cows; 350 tons of hay.

Foundation and first story, cement wall 9 feet above cement floor.

Supports, 4 × 8s, placed just back of stanchions, 3 feet on center.

Studs, 2 × 10s, 26 feet long, placed 2½ feet on center.




FIG. 42. ARRANGEMENT OF COW STABLE IN BARN NO. 6.

Joists 3×12 s, 20 feet long, 14 inches on center for main span.

Rafters, self-supporting. Sheathed with 1×6 s with no space between. This roof has a purline plate thrown in the gambrel. The plate is supported only by the braces which tie the joints.

The barn has been racked three times by the wind, replumbed and heavy iron rods put in to brace it, yet it is out of plumb at the present time.

CONCLUSIONS

In summing up the data given in this bulletin, it is obvious that the advantages of the round barn are convenience, strength, and cheapness.

The round barn is the more convenient, because of the unobstructed mow, which reduces the labor required in mowing hay, and because of the greater ease and fewer steps with which the feed can be gotten to the cows, owing to the central location of the supply.

The circular construction is the strongest because advantage is taken of the lineal strength of the lumber. All exposed surfaces are circular, and withstand greater wind pressure, as the wind can get no direct hold, as on the sides or gable ends of a rectangular barn.

In round numbers, rectangular barns require, according to their construction, from 34 to 58 percent more in cost of material than round barns with the same floor area and built of the same grade of material.

TRANSCRIBER NOTES:

Punctuation has been normalized without note.

Scale references in photos have not been retained.

Footnotes have been moved to the end of each section.

Hyphenation of words has been changed to be more consistent throughout the text.

Some page numbers are missing due to movement of tables from their original location.

Page 6: "betwen" changed to "between" (midway between the silo and the outside wall).

*** END OF THE PROJECT GUTENBERG EBOOK
ECONOMY OF THE ROUND DAIRY BARN ***

Updated editions will replace the previous one—the old editions will be renamed.

Creating the works from print editions not protected by U.S. copyright law means that no one owns a United States copyright in these works, so the Foundation (and you!) can copy and distribute it in the United States without permission and without paying copyright royalties. Special rules, set forth in the General Terms of Use part of this license, apply to copying and distributing Project Gutenberg™ electronic works to protect the PROJECT GUTENBERG™ concept and trademark. Project Gutenberg is a registered trademark, and may not be used if you charge for an eBook, except by following the terms of the trademark license, including paying royalties for use of the Project Gutenberg trademark. If you do not charge anything for copies of this eBook, complying with the trademark license is very easy. You may use this eBook for nearly any purpose such as creation of derivative works, reports, performances and research. Project Gutenberg eBooks may be modified and printed and given away—you may do practically ANYTHING in the United States with eBooks not protected by U.S. copyright law. Redistribution is subject to the trademark license, especially commercial redistribution.

START: FULL LICENSE

THE FULL PROJECT GUTENBERG™ LICENSE

PLEASE READ THIS BEFORE YOU DISTRIBUTE OR USE THIS WORK

To protect the Project Gutenberg™ mission of promoting the free distribution of electronic works, by using or distributing this work (or any other work associated in any way with the phrase “Project Gutenberg”), you agree to comply with all the terms of the Full Project Gutenberg License available with this file or online at www.gutenberg.org/license.

Section 1. General Terms of Use and Redistributing Project Gutenberg electronic works

1.A. By reading or using any part of this Project Gutenberg electronic work, you indicate that you have read, understand, agree to and accept all the terms of this license and intellectual property (trademark/copyright) agreement. If you do not agree to abide by all the terms of this agreement, you must cease using and return or destroy all copies of Project Gutenberg electronic works in your possession. If you paid a fee for obtaining a copy of or access to a Project Gutenberg electronic work and you do not agree to be bound by the terms of this agreement, you may obtain a refund from the person or entity to whom you paid the fee as set forth in paragraph 1.E.8.

1.B. “Project Gutenberg” is a registered trademark. It may only be used on or associated in any way with an electronic work by people who agree to be bound by the terms of this agreement. There are a few things that you can do with most Project Gutenberg electronic works even without complying with the full terms of this agreement. See paragraph 1.C below. There are a lot of things you can do with Project Gutenberg electronic works if you follow the terms of this agreement and help preserve free future access to Project Gutenberg electronic works. See paragraph 1.E below.

1.C. The Project Gutenberg Literary Archive Foundation (“the Foundation” or PGLAF), owns a compilation copyright in the collection of Project Gutenberg electronic works. Nearly all the individual works in the collection are in the public domain in the United States. If an individual work is unprotected by copyright law in the United States and you are located in the United States, we do not claim a right to prevent you from copying, distributing, performing, displaying or creating derivative works based on the work as long as all references to Project Gutenberg are removed. Of course, we hope that you will support the Project Gutenberg mission of promoting free access to electronic works by freely sharing Project Gutenberg works in compliance with the terms of this agreement for keeping the Project Gutenberg name associated with the work. You can easily comply with the terms of this agreement by keeping this work in the same format with its attached full Project Gutenberg License when you share it without charge with others.

1.D. The copyright laws of the place where you are located also govern what you can do with this work. Copyright laws in most countries are in a constant state of change. If you are outside the United States, check the laws of your country in addition to the terms of this agreement before downloading, copying, displaying, performing, distributing or creating derivative works based on this work or any other Project Gutenberg work. The Foundation makes no representations concerning the copyright status of any work in any country other than the United States.

1.E. Unless you have removed all references to Project Gutenberg:

1.E.1. The following sentence, with active links to, or other immediate access to, the full Project Gutenberg License must appear prominently whenever any copy of a Project Gutenberg work (any work on which the phrase “Project Gutenberg” appears, or with which the phrase

“Project Gutenberg” is associated) is accessed, displayed, performed, viewed, copied or distributed:

This eBook is for the use of anyone anywhere in the United States and most other parts of the world at no cost and with almost no restrictions whatsoever. You may copy it, give it away or re-use it under the terms of the Project Gutenberg™ License included with this eBook or online at www.gutenberg.org. If you are not located in the United States, you will have to check the laws of the country where you are located before using this eBook.

1.E.2. If an individual Project Gutenberg electronic work is derived from texts not protected by U.S. copyright law (does not contain a notice indicating that it is posted with permission of the copyright holder), the work can be copied and distributed to anyone in the United States without paying any fees or charges. If you are redistributing or providing access to a work with the phrase “Project Gutenberg” associated with or appearing on the work, you must comply either with the requirements of paragraphs 1.E.1 through 1.E.7 or obtain permission for the use of the work and the Project Gutenberg trademark as set forth in paragraphs 1.E.8 or 1.E.9.

1.E.3. If an individual Project Gutenberg electronic work is posted with the permission of the copyright holder, your use and distribution must comply with both paragraphs 1.E.1 through 1.E.7 and any additional terms imposed by the copyright holder. Additional terms will be linked to the Project Gutenberg License for all works posted with the permission of the copyright holder found at the beginning of this work.

1.E.4. Do not unlink or detach or remove the full Project Gutenberg License terms from this work, or any files

containing a part of this work or any other work associated with Project Gutenberg.

1.E.5. Do not copy, display, perform, distribute or redistribute this electronic work, or any part of this electronic work, without prominently displaying the sentence set forth in paragraph 1.E.1 with active links or immediate access to the full terms of the Project Gutenberg License.

1.E.6. You may convert to and distribute this work in any binary, compressed, marked up, nonproprietary or proprietary form, including any word processing or hypertext form. However, if you provide access to or distribute copies of a Project Gutenberg work in a format other than “Plain Vanilla ASCII” or other format used in the official version posted on the official Project Gutenberg website (www.gutenberg.org), you must, at no additional cost, fee or expense to the user, provide a copy, a means of exporting a copy, or a means of obtaining a copy upon request, of the work in its original “Plain Vanilla ASCII” or other form. Any alternate format must include the full Project Gutenberg License as specified in paragraph 1.E.1.

1.E.7. Do not charge a fee for access to, viewing, displaying, performing, copying or distributing any Project Gutenberg works unless you comply with paragraph 1.E.8 or 1.E.9.

1.E.8. You may charge a reasonable fee for copies of or providing access to or distributing Project Gutenberg electronic works provided that:

- You pay a royalty fee of 20% of the gross profits you derive from the use of Project Gutenberg works calculated using the method you already use to calculate your applicable taxes. The fee is owed to the owner of the Project Gutenberg trademark, but he has agreed to donate royalties under this paragraph to the Project Gutenberg Literary Archive Foundation. Royalty payments must be

paid within 60 days following each date on which you prepare (or are legally required to prepare) your periodic tax returns. Royalty payments should be clearly marked as such and sent to the Project Gutenberg Literary Archive Foundation at the address specified in Section 4, “Information about donations to the Project Gutenberg Literary Archive Foundation.”

- You provide a full refund of any money paid by a user who notifies you in writing (or by e-mail) within 30 days of receipt that s/he does not agree to the terms of the full Project Gutenberg™ License. You must require such a user to return or destroy all copies of the works possessed in a physical medium and discontinue all use of and all access to other copies of Project Gutenberg™ works.
- You provide, in accordance with paragraph 1.F.3, a full refund of any money paid for a work or a replacement copy, if a defect in the electronic work is discovered and reported to you within 90 days of receipt of the work.
- You comply with all other terms of this agreement for free distribution of Project Gutenberg™ works.

1.E.9. If you wish to charge a fee or distribute a Project Gutenberg™ electronic work or group of works on different terms than are set forth in this agreement, you must obtain permission in writing from the Project Gutenberg Literary Archive Foundation, the manager of the Project Gutenberg™ trademark. Contact the Foundation as set forth in Section 3 below.

1.F.

1.F.1. Project Gutenberg volunteers and employees expend considerable effort to identify, do copyright research on, transcribe and proofread works not protected by U.S. copyright law in creating the Project Gutenberg™ collection. Despite these efforts, Project Gutenberg™ electronic works, and the medium on which they may be stored, may contain “Defects,” such as, but not limited to,

incomplete, inaccurate or corrupt data, transcription errors, a copyright or other intellectual property infringement, a defective or damaged disk or other medium, a computer virus, or computer codes that damage or cannot be read by your equipment.

1.F.2. LIMITED WARRANTY, DISCLAIMER OF DAMAGES - Except for the “Right of Replacement or Refund” described in paragraph 1.F.3, the Project Gutenberg Literary Archive Foundation, the owner of the Project Gutenberg™ trademark, and any other party distributing a Project Gutenberg™ electronic work under this agreement, disclaim all liability to you for damages, costs and expenses, including legal fees. YOU AGREE THAT YOU HAVE NO REMEDIES FOR NEGLIGENCE, STRICT LIABILITY, BREACH OF WARRANTY OR BREACH OF CONTRACT EXCEPT THOSE PROVIDED IN PARAGRAPH 1.F.3. YOU AGREE THAT THE FOUNDATION, THE TRADEMARK OWNER, AND ANY DISTRIBUTOR UNDER THIS AGREEMENT WILL NOT BE LIABLE TO YOU FOR ACTUAL, DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE OR INCIDENTAL DAMAGES EVEN IF YOU GIVE NOTICE OF THE POSSIBILITY OF SUCH DAMAGE.

1.F.3. LIMITED RIGHT OF REPLACEMENT OR REFUND - If you discover a defect in this electronic work within 90 days of receiving it, you can receive a refund of the money (if any) you paid for it by sending a written explanation to the person you received the work from. If you received the work on a physical medium, you must return the medium with your written explanation. The person or entity that provided you with the defective work may elect to provide a replacement copy in lieu of a refund. If you received the work electronically, the person or entity providing it to you may choose to give you a second opportunity to receive the work electronically in lieu of a refund. If the second

copy is also defective, you may demand a refund in writing without further opportunities to fix the problem.

1.F.4. Except for the limited right of replacement or refund set forth in paragraph 1.F.3, this work is provided to you ‘AS-IS’, WITH NO OTHER WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE.

1.F.5. Some states do not allow disclaimers of certain implied warranties or the exclusion or limitation of certain types of damages. If any disclaimer or limitation set forth in this agreement violates the law of the state applicable to this agreement, the agreement shall be interpreted to make the maximum disclaimer or limitation permitted by the applicable state law. The invalidity or unenforceability of any provision of this agreement shall not void the remaining provisions.

1.F.6. INDEMNITY - You agree to indemnify and hold the Foundation, the trademark owner, any agent or employee of the Foundation, anyone providing copies of Project Gutenberg™ electronic works in accordance with this agreement, and any volunteers associated with the production, promotion and distribution of Project Gutenberg™ electronic works, harmless from all liability, costs and expenses, including legal fees, that arise directly or indirectly from any of the following which you do or cause to occur: (a) distribution of this or any Project Gutenberg work, (b) alteration, modification, or additions or deletions to any Project Gutenberg work, and (c) any Defect you cause.

Section 2. Information about the Mission of Project Gutenberg

Project Gutenberg is synonymous with the free distribution of electronic works in formats readable by the

widest variety of computers including obsolete, old, middle-aged and new computers. It exists because of the efforts of hundreds of volunteers and donations from people in all walks of life.

Volunteers and financial support to provide volunteers with the assistance they need are critical to reaching Project Gutenberg's goals and ensuring that the Project Gutenberg collection will remain freely available for generations to come. In 2001, the Project Gutenberg Literary Archive Foundation was created to provide a secure and permanent future for Project Gutenberg and future generations. To learn more about the Project Gutenberg Literary Archive Foundation and how your efforts and donations can help, see Sections 3 and 4 and the Foundation information page at www.gutenberg.org.

Section 3. Information about the Project Gutenberg Literary Archive Foundation

The Project Gutenberg Literary Archive Foundation is a non-profit 501(c)(3) educational corporation organized under the laws of the state of Mississippi and granted tax exempt status by the Internal Revenue Service. The Foundation's EIN or federal tax identification number is 64-6221541. Contributions to the Project Gutenberg Literary Archive Foundation are tax deductible to the full extent permitted by U.S. federal laws and your state's laws.

The Foundation's business office is located at 41 Watchung Plaza #516, Montclair NJ 07042, USA, +1 (862) 621-9288. Email contact links and up to date contact information can be found at the Foundation's website and official page at www.gutenberg.org/contact

Section 4. Information about Donations to the Project Gutenberg Literary Archive Foundation

Project Gutenberg™ depends upon and cannot survive without widespread public support and donations to carry out its mission of increasing the number of public domain and licensed works that can be freely distributed in machine-readable form accessible by the widest array of equipment including outdated equipment. Many small donations (\$1 to \$5,000) are particularly important to maintaining tax exempt status with the IRS.

The Foundation is committed to complying with the laws regulating charities and charitable donations in all 50 states of the United States. Compliance requirements are not uniform and it takes a considerable effort, much paperwork and many fees to meet and keep up with these requirements. We do not solicit donations in locations where we have not received written confirmation of compliance. To SEND DONATIONS or determine the status of compliance for any particular state visit www.gutenberg.org/donate.

While we cannot and do not solicit contributions from states where we have not met the solicitation requirements, we know of no prohibition against accepting unsolicited donations from donors in such states who approach us with offers to donate.

International donations are gratefully accepted, but we cannot make any statements concerning tax treatment of donations received from outside the United States. U.S. laws alone swamp our small staff.

Please check the Project Gutenberg web pages for current donation methods and addresses. Donations are accepted in a number of other ways including checks, online payments and credit card donations. To donate, please visit: www.gutenberg.org/donate.

Section 5. General Information About Project Gutenberg electronic works

Professor Michael S. Hart was the originator of the Project Gutenberg concept of a library of electronic works that could be freely shared with anyone. For forty years, he produced and distributed Project Gutenberg eBooks with only a loose network of volunteer support.

Project Gutenberg eBooks are often created from several printed editions, all of which are confirmed as not protected by copyright in the U.S. unless a copyright notice is included. Thus, we do not necessarily keep eBooks in compliance with any particular paper edition.

Most people start at our website which has the main PG search facility: www.gutenberg.org.

This website includes information about Project Gutenberg, including how to make donations to the Project Gutenberg Literary Archive Foundation, how to help produce our new eBooks, and how to subscribe to our email newsletter to hear about new eBooks.